

idealpos®

Idealpos i15

High-Performing Touchscreen POS Terminal

Lasting
4-7 years*



Key Features



15" Zero-Bezel
with PCAP
Touch



Intel® CPU



FANLESS



Flexible
Peripheral
Support



Die-Cast
Aluminium
Housing

www.idealpos.co

*Subject to usage.

Technical Specifications

Touch Panel	True Flat Projected Capacitive Touch
Display	15" TFT LCD Panel (LED Backlight)
Resolution	1024 x 768 Pixels
Brightness	250nits
Intel® Processor	Intel® CPU
Memory	4GB DDR3 SO-DIMM RAM
Storage	60GB 2.5" Solid State Hard Drive
Power Supply	65W External Adaptor. Voltage + 19VDC 3.42A max.
Operating System	Windows® 10 Inudstry Retail Pro Embedded
System Dimensions	370 x 300 x 236mm
System Weight	5.68kg
VESA Mount	VESA 100*100mm compliant
Product Certification	CE / FCC / ROHS
Operating Temperature	0°C to 40°C
USB Port	4 x USB 2.0, 1 x USB 3.0
Serial Port	2 x RS-232 (RJ48 connector) 1 x RS-232 (DB9 connector)
Network LAN	1 x Gigabit Ethernet RJ45
Audio	HD Audio, 2W Speakers x 2
VGA Display	1 x DB-15 VGA Port
Cash Drawer	1 x RJ-11 (12v or 24v) Dafult is 12v

Accessories

Magnetic Card Reader	3 Track Serial Interface
RFID Clerk Wristband Reader	125Khz Frequency
MSR/RFID Combo	Magnetic Card Reader and RFID Combo
Customer Display	7" or 10.1" LED Customer Display
1D/2D Scanner	Integrated 1D/2D Barcode Scanner

Intel and Intel Atom is a trademark of Intel Corporation in the U.S. and/or other countries. Microsoft and Windows are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.

idealpos[®]

www.idealpos.co