

idealpos[®]

Idealpos Audrey

Stylish and Slim Touchscreen POS Terminal



Lasting
4-7 years*



Key Features



10-point
PCAP touch



Intel® CPU



FANLESS



Flexible
Peripheral
Support



Aluminium
stand, plastic
frame

www.idealpos.co

*Subject to usage.

Technical Specifications

| | |
|------------------------|--|
| Display | 15.6", Resolution 1366 x 768 (220 nits) or 15.6" Resolution 1920 x 1080 (300 nits) |
| Touch | PCAP |
| CPU | Intel® Core™ i5-6300U Processor (SKYLAKE-U Co-lay) Intel® Core™ i3-6100U Processor (SKYLAKE-U Co-lay) Intel Celeron Processor 3955U (SKYLAKE-U Co-lay) Intel Celeron 3965U (KABYLAKE-U Co-lay) Intel® Core™ i3-7100U (KABYLAKE-U Co-lay) Intel® Core™ i5-7300U (KABYLAKE-U Co-lay) |
| Memory | DDR4 4GB, 8GB, 16GB |
| Storage | M.2 PCIe Gen3.0 x2 SSD: 128G / 256G |
| External I/O Interface | 2 x Serial ports, RS232 (RJ45), 0V/5V/12V selection by BIOS (COM1, COM2) 2 x LAN (IEEE 802.3 10/100/1000 Mbps Ethernet, RJ45) 1 x RJ11 port supports 2 cash drawer with 24V / 12V by jumper setting 1 x DC+12V out 4 x USB 3.0 (USB3.0/2.0) 1 x DC +12V input 1 x Audio (1 x Line-out) 1 x HDMI 1 x VGA |
| Speaker | 1 x Speaker 3W |
| WIFI/BT | Option |
| Display Support | 3 Independent Displays (Main Display + VGA + HDMI) |
| Operation System | 1. POS Ready7 (32bit & 64bit) SKYLAKE CPU only 2. Windows 10 IoT LTSB (64bit) 3. Linux (Ubuntu) |
| Power Adaptor | AC-In 100~240V / DC-Out 12V, 90W |
| Dimensions | 392mm(W) x 321mm(H) x 201mm(D) |
| Peripheral | Encryption-capable MSR, EMV reader, Bio reader, NFC, iButton, camera, 2D BCR, VFD, 10.1", 11.6", 15" guest facing display |

idealpos[®]

www.idealpos.co